



UL Online Certifications Directory

[Home](#) [Quick Guide](#) [Contact Us](#) [UL.com](#)

ZPMV2.E71379 Wiring, Printed - Component

Enhanced searching capability for this category can be found in UL's iQ Family of Databases ([iq.ul.com](#)).

Enhanced searching capability for this category can be found in UL's iQ Family of Databases ([iq.ul.com](#)).

[Page Bottom](#)

Wiring, Printed - Component

[See General Information for Wiring, Printed - Component](#)

K & F ELECTRONICS INC

E71379

33041-45 GROESBECK HWY

FRASER, MI 48026 USA

Type	Cond Width		Cond	SS/ DS/ DSO	Max Area Diam mm(in)	Max		Max Oper Temp C	Meets UL796 UL796 Class	C
	Min	Edge				Solder	Flame			
	mm(in)	mm(in)				Limits C sec	UL796 DSR			
Multilayer printed wiring boards.										
2-0	0.07 (0.003)	0.07 (0.003)	18 (0.71)	DS	50.8 (2.0)	288	10	130	V-0	All *
4-0	0.07 (0.003)	0.07 (0.003)	18 (0.71)	DS	101.6 (4.0)	288	10	130	V-0	All *
6	0.13 (0.005)	0.38 (0.015)	16.5 (0.65)	DS	76.2 (3.0)	260	10	130	V-0	All -
B	0.05 (0.002)	0.05 (0.002)	17 (0.67) Int:68	DS	50.8 (2.0)	260	20	130	V-0	All -
J-2	0.10 (0.004)	0.18 (0.007)	16.5 (0.65)	DS	25.4 (1.0)	274	15	130	V-0	All -
J-M	0.10 (0.004)	0.20 (0.008)	17 (0.67)	DS	75 (3.0)	260	10	105	V-0	All -
M-1	0.1 (0.004)	0.15 (0.006)	17 (0.67)	DS	90 (3.5)	288	10	130	V-0	All *
M-	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All -


10			Int:213								
M-9	0.10 (0.004)	0.15 (0.006)	17 (0.67) Int:68	DS	76.2 (3.0)	260	10	130	V-0	All	-
M-99	0.10 (0.004)	0.15 (0.006)	17 (0.67) Int:68	DS	25.4 (1.0)	260	10	130	V-0	All	-
M-V0	0.08 (0.003)	0.18 (0.007)	17 (0.67) Int:68	SS	76.2 (3.0)	260	10	105	V-0	All	-
M0-V0	0.04 (0.002)	0.07 (0.003)	17 (0.67) Int:68	SS	76.2 (3.0)	288	10	130	V-0	All	-

Single layer printed wiring boards.

1	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	101.6 (4.0)	274	10	130	-	-	*
1-0	0.12 (0.005)	0.12 (0.005)	17 (0.67)	DS	101.6 (4.0)	274	10	130	V-0	All	*
1V-0	0.03 (0.001)	0.03 (0.001)	16.5 (0.65)	DS	50.8 (2.0)	260	20	130	V-0	All	-
2	0.25 (0.010)	0.76 (0.030)	16.5 (0.65)	DS	63.5 (2.5)	260	10	130	V-0	□	-
2V-0	0.15 (0.006)	0.05 (0.002)	16.5 (0.65)	DS	50.8 (2.0)	260	20	120	V-0	All	-
3	0.13 (0.005)	0.23 (0.009)	16.5 (0.65)	DS	76.2 (3.0)	260	10	150	V-0	All	-
3-0	0.07 (0.003)	0.17 (0.007)	34.3 (1.35)	DS	76.2 (3.0)	288	10	130	V-0	All	*
4	0.1 (0.004)	0.1 (0.004)	16.5 (0.65)	DS	304.8 (12.0)	260	10	105	V-0	-	-
5	0.13 (0.005)	0.15 (0.006)	33 (1.30)	DS	25.4 (1.0)	260	10	130	V-0	-	-
7	0.13 (0.005)	0.23 (0.009)	16.5 (0.65)	DS	76.2 (3.0)	260	10	105	V-0	-	-
A	0.25 (0.010)	0.76 (0.030)	16.5 (0.65)	DS	63.5 (2.5)	260	10	130	V-0	All	-
D-1	0.1 (0.004)	0.15 (0.006)	17 (0.67)	DS	90 (3.5)	288	10	130	V-0	All	*
D-10	0.10 (0.004)	0.15 (0.006)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	-
D-9	0.10 (0.004)	0.15 (0.006)	17 (0.67)	DS	76.2 (3.0)	260	10	130	V-0	All	-
D-V0	0.08 (0.003)	0.18 (0.007)	17 (0.67)	DS	76.2 (3.0)	260	10	105	V-0	All	-
D-V0 (SS)	0.14 (0.006)	0.20 (0.008)	34 (1.34)	SS	25.4 (1.0)	260	10	130	V-0	All	-
D0-V0	0.04 (0.002)	0.07 (0.003)	17 (0.67)	DS	76.2 (3.0)	288	10	130	V-0	All	-
J-2	0.13 (0.005)	0.20 (0.008)	17 (0.67)	DS	25.4 (1.0)	260	10	130	V-0	All	-

LD	0.18 (0.007)	0.38 (0.015)	-	DS	25.4 (1.0)	274	10	130	-	-	-
LD-1	0.18 (0.007)	0.38 (0.015)	1.3 (0.05)	SS	25.4 (1.0)	260	10	130	V-0	-	-
LD-O	0.18 (0.007)	0.38 (0.015)	-	DS	25.4 (1.0)	274	10	130	V-0	-	-

* - CTI PLC is marked on individual board.

Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

[Last Updated](#) on 2013-03-27

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".